

WARNING:

Validate the kit contents with the component list included on page 2 of this sheet before proceeding. This kit is intended to be used in a modified vehicle. Please read this sheet thoroughly and be sure that you understand everything explained on it prior to opening any of the enclosed packages, or before attempting to install any of the components. Once this kit has been opened or a component installed, the kit is not returnable.

- 1. This kit should typically be used in a **MODIFIED** application only.
- 2. This kit supports the use of factory heater systems and aftermarket heater and A/C systems. The kit supplies power to a factory A/C control head but DOES NOT include the actual A/C harness for an original factory A/C vehicle. Factory original A/C harnesses are available under our Factory Fit product line as they are self contained harnesses made to fit and work with the stock A/C component configuration.
- 3. This kit supports the use of a high current self-exciting 1-wire alternator or other style internally regulated alternators. An adapter may be necessary in some applications. The use of a stock, low amperage alternator is seriously discouraged as they cannot handle the higher current requirements of updated ignition systems, electric fans, aftermarket A/C systems, stereo systems, air ride suspensions, and other power hungry accessories and will ultimately create performance issues with the system.
- 4. This kit **WILL NOT** support the use of a factory ammeter. All AAW kits are engineered to supply the optimum charge to the battery. To achieve this performance, we route our 6ga. charge wire directly from the alternator output charge terminal to the starter battery termial. Due to the path of the charge being altered from the stock configuration, the gauge can no longer see a charge vs. a discharge, so it will not work properly. When ammeters were originally used, most generator or alternator current outputs were rated at a maximum of about 25-60 amps. Modified cars being built today typically utilize a 100 amp or higher output alternator. With these higher current units, ammeters, generally speaking, become a safety hazard. Ammeters are usually wired in parallel to the charging circuit, are typically unfused, and can short very easily causing a fire. A voltmeter is recommended as a good alternative.
- 5. This kit IS NOT set up with a resistance wire for a standard, points type ignition system. It is wired with a full 12 volt primary ignition feed that is hot in the run position. Primary ignition voltage in the starting position is handled via a full 12 volt bypass wire. Our system will support HEI, MSD, other electronic ignition systems, as well as most all computerized Fuel Injection systems. If you wish to run a points type system, there are illustrations on the engine connection pages to do so. Extra parts (ballist resistor) that are not included in this kit will be required to complete that operation.



500560 - Classic Update Series Kit 1960-66 Chevrolet Truck

This kit contains the following components:

	Part		
<u>Bag</u>	<u>Number</u>	<u>Description</u>	Quantity
	500042	Floor Dimmer Switch	1
	500332	Headlight Switch	1
J	500551	Engine Wiring Kit	1
L	500558	Front Light Wiring Kit	1
G	500559	Dash Harness Kit	1
M	500561	Rear Body Wiring Kit	1
Н	500608	Instrument Cluster wiring kit	1
Р	500611	Heater Kit	1
Ο	500613	Wiper Kit	1
Ν	500614	Courtesy Light Kit	1
	500674	Key and tumbler assy.	1
	510632	Ignition Switch	1
	500919	Practice Terminal Crimping Set	1
	510565	Fuse, Relay, and Flasher Kit	1
Z	510476	Alternator and Main Power Connection kit	t 1
	92965659	Kit Introduction Instruction Sheet	1
	92970001	Warning Sheet	1

Validate the kit contents with this component list. If there are any discrepancies with incorrect or missing parts, stop your installation and notify the supplier you purchased the kit from before proceeding.



www.americanautowire.com 856-933-0801

500560

92970001 instruction sheet Rev 4.0 9/26/2019